



PRODUCTS & SERVICES

CAPABILITIES STATEMENT



WE OPEN THE WAY

DIRECT HEAT 'RUBBERISED' CRACK AND JOINT SEALANT.

Elastomeric compound. Polymer modified.
100% water tight seal.
Traffic ready in 20 minutes.
Multi-use for asphalt and concrete.



TECHNOLOGY BREAKTHROUGH

Now for the first time, Industry professionals can get contractor type results in 3 easy steps using 3 tools. CRACKSTIX are available in two standard sizes, small 6mm and medium 12mm. They are User Friendly & Ready-To-Use: no mixing, nothing to add, just uncoil, cut to length, pack and heat.

CRACKSTIX are flexible & can be stretched & shaped to custom fit the repair. The rubberized compound melts/liquefies instantly & cures quickly. The self levelling sealant goes inside the crack.. not over the crack.. less waste, no tracking or unsightly residue. The multi-use formula can be used on asphalt & concrete pavements and is available in black and grey.

WHY HOT, DIRECT HEAT PROCESS?

In the past, most contractors have had no choice but to use cold pour or caulking type fillers. Cold applied products fill from the bottom up and do not permanently bond/seal to the crack sidewalls.

CRACKSTIX are hot applied, using a direct heat process CRACKSTIX form a permanent bond to the sidewalls of the crack or joint and provides a (liquid rubber) 100% water tight seal. This seal will remain flexible & intact through the winter and summer expansion/contraction cycles.

APPLICATIONS

ASPHALT TO CONCRETE



ASPHALT TO ASPHALT



CONCRETE TO CONCRETE



3 EASY STEPS



1. CLEAN IT

Take a screwdriver & scratch out all debris from inside the crack, then take a whisk broom & sweep it clean. Crack must be dry.

2. PACK IT

Uncoil & cut the appropriate size & shape/pack in to crack with fingertip pressure. Using the screwdriver, press the stix into crack approximately 1.5mm to 3mm below actual pavement surface level. To achieve a neat overall appearance, do not overfill crack. The material seals In It... Not On It.

3. MELT IT

take propane torch and light it. Adjust bright blue part of flame to 300mm long. Holding the flame 25mm - 40mm from stix, move the flame from side to side in a slow & even motion, heating no more than 300mm at a time (melt stick until liquid).



COLAS Australia Group Pty Ltd
3-5 Gibbon Road
Winston Hills NSW 2153
+61 2 9624 0100
+61 1300 0 COLAS (26527)
info@colas.com.au

www.colas.com.au

The material in this brochure is for information purposes only. COLAS does not guarantee that the information is complete or correct and does not accept any responsibility for loss or damage suffered by any person or body relying on any information contained. This brochure does not constitute advice and COLAS does not accept any liability for any decisions made on the basis. COLAS urges you to obtain your own advice with any selection or application of our products covered in this brochure.